

2200
ANSI LUMENS

MITSUBISHI X390U

Desktop Portable XGA LCD ColorView™ Projector

**Fully-Featured For
Maximum Versatility
And Reliability.**



True XGA

SXGA Maximum

2200 ANSI Lumens

Color Uniformity Correction

1500-Hour Lamp Life With Extended Life Mode

Exclusive, Award-Winning ColorView

Computers And HDTV-Ready



The X390U from Mitsubishi Digital Electronics is a high performance XGA LCD projector with a full feature set for reliable, worry-free presentations.

- Up to 2200 ANSI lumens for super bright presentations
- 400:1 contrast ratio for exceptional color depth and clarity
- Polysilicon three-panel LCD system
- Power zoom and focus adjustment
- Projects images from 40 inches to 300 inches; suitable for front, rear and ceiling mount installations
- 250-watt short-arc NSH lamp; 1500-hour lamp life with extended life mode
- Professional Presentation Features: Simultaneous live picture-in-picture, simultaneous video and RGB sourcing, intuitive on-screen graphic user-interface in seven languages, color temperature, built-in laser pointer, Cineview™ video line doubler, digital keystone adjustment, and digital zoom
- Exclusive, award-winning Colorview™ Natural Color Matrix for rich, vivid colors
- Direct access digital keystone correction
- RS-232 communication terminal (PC and MAC) for seamless system integration
- Simple, one-touch auto set-up function; plug and play compatibility supporting two computer and two video inputs simultaneously
- Accepts S-VHS, NTSC, NTSC 4.43, PAL and SECAM video formats, DVD, HDTV-ready and computer inputs from Apple®, IBM®, and many workstation computers
- Three-year parts and labor warranty, 90-day warranty on the lamp, toll-free support plus an exclusive 3-year Emergency Roadside Assistance (ERA) program that guarantees free replacement product shipped overnight for next business-day delivery when and where available




MITSUBISHI
PRESENTATION PRODUCTS
Innovation On Display_{sm}

MITSUBISHI X390U

DESKTOP PORTABLE XGA LCD COLORVIEW™ PROJECTOR

2200
ANSI LUMENS



1. Wired Remote Control Input
2. Digital/Analog Select
3. Digital Video Interface (DVI)
4. RS-232 Input
5. USB Input
6. Video/Audio Inputs (Composite RCA/BNC)
7. Audio Inputs (2) And Output
8. Computer Monitor Output
9. Computer 1 & 2 In/Component Video
10. Power Jack
11. Ground Terminal
12. Main Power

FULLY-FEATURED VERSATILITY

Brightness
2200 ANSI Lumens

Colors
Exclusive ColorView™

Warranty
3-years


Service
Exclusive 3-year ERA

Connections
Computers and HDTV-Ready

SPECIFICATIONS

Display Technology	1.3" x 3 Polysilicon LCD panel
Resolution	True XGA 1024 x 768 with compression for SXGA 1280 x 1024 maximum; 540 video lines
Brightness (ANSI Lumens)	2200
Colors	Exclusive Mitsubishi ColorView™ Natural Color Matrix supports 16.7 million colors (32-bit). Red, green, blue, cyan, yellow, magenta axis are independently adjustable; includes saturation adjustment.
Contrast Ratio	400:1
Lens	Power zoom and focus. All glass lens assembly. (zoom ratio: 1.26:1) F = 1.8 - 2.2; f = 52- 66 mm
Picture Size	40" - 300" diagonal (aspect ratio 4:3 default, 16:9 anamorphic video option)
Picture-In-Picture	Swappable simultaneous live video and computer display (5 P-I-P display modes)
Lamp	Type: 250-watt short-arc NSH lamp; 1500 hours lamp life (user changeable) with extended life mode
Computer Compatibility	PCs, Macintosh® computers, workstations up to 1280 x 1024; supports sync on green
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL M, PAL N, SECAM, PAL 60, DVD component video, HDTV-ready up to 1080i
Input Terminals	<ul style="list-style-type: none"> • Computer; mini D-sub 15 pin x 2 • PC Audio; stereo mini jack x 2 • Video; BNC x 1 + SVHS x 1 • Video; RCA x 1 + SVHS x 1 • Video Audio; stereo RCA x 2
Output Terminals	<ul style="list-style-type: none"> • Computer; mini D-sub 15 pin x 1 • Audio (3.5 mm)
Communication Terminals	RS-232C x 1 (direct command is available); Wired remote terminal x 1; USB terminal for mouse; PS2 (mouse function)
Scanning Rates	H: 15 - 92 kHz; V: 50 - 85 Hz; Dot Clock: 160 MHz
Audio	2 x 2W stereo
Remote Control/Laser Pointer	Wireless remote with direct input access. Full projector and computer control with built-in mouse and laser pointer.
Height Adjuster	Two quick release legs (0-7° variable)
Weight	14.7 lbs. (6.7 kgs) Net
Dimensions (W x H x D)	11.8 x 5.2 x 14.5" (299 x 133 x 367 mm) (excluding legs and lens)
Power	AC 100 - 240V ±10%, 50/60 Hz
Power Consumption	360 watts
Kensington Lock-Ready	Protects from theft or preventable losses.
Safety Approvals	CSA, CSA NRT L/C, FCC Class-A
Warranty	Three-year parts and labor; 90 days on lamp. Also includes three-year Emergency Roadside Assistance program that guarantees free replacement projector shipped overnight for next business day delivery when and where available.
Accessories	<p>Standard AC power cable; RGB cable; Mac adapter for RGB cable; RS-232C cable; Mac adapter for RS-232C cable; USB cable; remote control; wired cable for remote unit; mouse adapter (PC and Mac); lens cap; and user manual.</p> <p>Optional User replaceable spare lamp (VLT-X400LP), ceiling mount kit (X400CM). Optional lenses are available from Buhl Optical.</p>
Other Special Features	Simultaneous live, swappable, picture-in-picture, simultaneous video and RGB sourcing, intuitive on-screen graphic user interface in seven languages, color temperature, built-in laser pointer, CineView™ Video Line Doubler, direct access digital keystone correction, Point-n-Zoom Digital Magnification and exclusive ColorView Natural Color Matrix.

For more information on the X390U or any of Mitsubishi's other projectors or presentation products, contact Mitsubishi Digital Electronics today. Detailed technical specifications available upon request.
Projector Part Number: LVPX390U



STANDARD PROJECTION THROW DISTANCE CHART

Diagonal Size (inch)	Screen		Distance from screen (L)/(Approximate)			
	Height (inch)	Width (inch)	Maximum zoom (cm)	Maximum zoom (inch)	Minimum zoom (cm)	Minimum zoom (inch)
40"	24"	32"	155	61"	195	77"
60"	36"	48"	235	92"	296	116"
80"	48"	64"	315	124"	396	156"
100"	60"	80"	394	155"	496	195"
120"	72"	96"	474	187"	597	235"
140"	84"	112"	554	218"	697	274"
160"	96"	128"	634	250"	797	314"
180"	108"	144"	714	281"	898	353"
200"	120"	160"	794	312"	998	393"
300"	180"	240"	1194	470"	-	-

The above numbers are approximate and may be slightly different than the actual measurements

©2000 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc, registered in the U.S. and other countries. All other trademarks or registered trademarks are the property of their respective holders.

Printed on 50% recycled paper including 20% post-consumer fibers, processed chlorine free. Printed with vegetable based inks.

Mitsubishi Digital Electronics America, Inc.
Presentation Products Division
9351 Jeronimo Road
Irvine, CA 92618
Telephone: 888-880-6351

Canada:
Mitsubishi Electric Sales Canada Inc.
Information Technologies Group
Markham, Ontario 905-475-7728

World Wide Web:
<http://www.mitsubishi-presentations.com>

MITSUBISHI
PRESENTATION PRODUCTS
Innovation On Display_{sm}